

P3.91 MM

**INDOOR NOVASTAR**

Front Service / Back Service

- Turn-key solution.
- Easy installation.
- Ground support compatible.
- Technical support available.
- 24 months warranty included for all parts. USA based.
- In stock. Ships immediately.



OPEN BACK ▲

▲ BACK DESIGN

**TECHNICAL SPECIFICATIONS**

PIXEL PITCH	P3.91 mm
LED ENCAPSULATION	King-Light SMD2020
PIXEL DENSITY	128 x 256
SIZE	500 x 1000 x 75mm / 19.7" x 39.4" x 3"
CHIP	IC2153
HIGH REFRESH RATE	3840hz
WEIGHT	32 lbs./ 15 Kg
RECEIVING CARD	NovaStar

## POWER SUPPLY

OPERATION POWER	100~240V 50-60Hz
MAX. POWER CONSUMPTION	200W/per panel
AVE. POWER CONSUMPTION	120W/per panel
CONNECTIONS POWER/DATA	Power-PowerCon In/Out; Data EtherCon In/Out

## OPTICAL RATINGS

BRIGHTNESS	1500 NITS
PROTECTION RATE	IP45
SCAN	1/16
FRAME FREQUENCY	60 Hz
VIEW ANGLE	Horizontal 140°/Vertical 140°
OPTIMAL VIEW DISTANCE	8 ft (2.4m)
BRIGHTNESS ADJUSTMENT	0~100% 100 Levels

