



INDOOR  
LED SCREEN PANEL P1.56

Produced by  MIRACLE®

# HOME LED WALL





INDUSTRY-LEADING  
QUALITY COMPONENTS.



3-YEAR WARRANTY  
FOR ALL PARTS.



**INDOOR  
LED PANEL**

Panel ideal for indoor  
LED video walls. Stand  
out in all the events  
ahead of you.




**BEST QUALITY  
RESOLUTION**

4K resolution panel  
designed for close  
viewing distances  
(minimum is 3ft).



**HIGH REFRESH  
RATE**

With 3840Hz the  
picture texture is clear  
and delicate, the  
color is vivid.



**PLUG AND  
PLAY**

Easy device recognition  
without configuration.  
Drivers are installed  
automatically.



HIGHLIGHTED  
COMPONENTS

INDOOR P1.56  
LED SCREEN PANEL



*Upgrade your living space into  
an infinite canvas of creativity  
with customizable LED panels*

**4K UHD**

HOME LED WALL

**NETFLIX**

**max**

**Roku**

**Apple tv**

**YouTube**





### GOB Mask

- + Anti reflection
- + Anti Moire effect

GOB is an improvement of traditional SMD technology, it is used for certain applications that require high-level protection of the LED front module. Used for broadcasting and virtual studios.

[WATCH VIDEO](#)



### USA-BASED COMPANY

Panel ideal for indoor LED video walls. Stand out in all the events ahead of you.



### TURN-KEY SOLUTIONS

LED video walls packages in stock, ready to ship immediately across the USA.



### EASY INSTALLATION

Connect the power cable, your HDMI device to the video processor and the ethernet port.



### TECHNICAL SUPPORT

We have online support with video tutorials, software, user guides, and specialized team.

## TECHNICAL SPECIFICATIONS



PIXEL PITCH	P1.56mm
LED ENCAPSULATION	King-Light SMD1212
PIXEL DENSITY	384 x 216
SIZE	600 x 337.5 x 75 mm / 23.6" x 13.3" x 3"
CHIP	ICN2065
HIGH REFRESH RATE	7680hz
WEIGHT	12 lb / pc - 5.5 kg
RECEIVING CARD	NovaStar A5s Plus



## HIGHLIGHTED COMPONENTS



### POWER SUPPLY

Slim bar with noiseless technology.




### RECEIVING CARD


#### A5s Plus NovaStar 7680 Hz

A general small receiving card developed by NovaStar. A single A5s Plus supports resolutions up to 512×384@60Hz. Supporting color management, 18bit+, pixel level brightness and chroma calibration, individual gamma adjustment for RGB, and 3D functions, the A5s Plus can significantly improve the display effect and user experience.





# PANEL DIMENSIONS



23,6 inches (60 cm)

13,3 inches (33,75 cm)

FRONT +  
MODULE  
SIZE



11,8 in (30 cm)

6,65 in  
(16,85 cm)



13,3 inches (33,75 cm)

SIDE +  
MODULE  
SIZE



6,65 in  
(16,85 cm)

3 in  
(7,5 cm)

1 in  
(2,5 cm)

## OPTICAL RATINGS




BRIGHTNESS	1000 NITS
PROTECTION RATE	IP45
SCAN	1/48s
FRAME FREQUENCY	60 Hz
VIEW ANGLE	Horizontal 160° / Vertical 160°
MINIMUM VIEW DISTANCE	3 ft (0.9 m)
BRIGHTNESS ADJUSTMENT	0~100% 100 Levels



MINIMUM  
VIEWING  
DISTANCE


WATCH VIDEO

OPTIMAL RANGE	3 ft.	4 ft.	5 ft.	6 ft.	10 ft.	15 ft.	20 ft.	25 ft.
PIXEL PITCH (mm)	P1.56	P1.86	P1.99	P2.5	P2.97	P3.91	P4.81	P5



## COMPATIBLE SUPPORTS

WATCH VIDEO



### WALL MOUNTABLE

It is the most common support and above all the most stable considering the type of construction where it is mounted, since it is screwed through the holes included in our panels.

## POWER SUPPLY




OPERATION POWER	100~240V 50-60Hz
POWER CONSUMPTION	200 W/pc
CONNECTIONS POWER/DATA	Power-PowerCon In/Out; Data EtherCon In/Out



## FRONT SERVICEABLE

Easily removable magnetic module system to simplify assembly, repair or replacement of components. They can be removed with a special tool or manually.





LED NATION



[www.lednationusa.com](http://www.lednationusa.com)



[info@lednationusa.com](mailto:info@lednationusa.com)



1 (888) 590-1720



STE 113 14501 NW 57th Ave,  
Opa-locka, FL 33054



OFFICIAL DEALER



MIRACKLE

