

CURVED



Produced by MIRACKLE

VIEW PACKAGES ONLINE







INDUSTRY-LEADING QUALITY COMPONENTS.

WATCH VIDEO P2.5MM



3-YEAR WARRANTY FOR ALL PARTS.



INDOOR LED PANEL

Panel ideal for indoor LED video walls. Stand out in all the events ahead of you.



BEST QUALITY RESOLUTION

4K resolution panel designed for close viewing distances (minimum is 6ft).



HIGH REFRESH RATE

With 3840Hz the picture texture is clear and delicate, the color is vivid.



PLUG AND PLAY

Easy device recognition without configuration. Drivers are installed automatically.








CURVED LED SCREEN PANEL


Inner curve max can be -20 degree (each side curve lock set -10. in actual use, usually no big curve angle in inner curve, because if the curve angle is big, we cannot remove a broken module and replace).


Outer curve max can be +10 degree (each side curve lock set +5).











GOB Mask

- + Anti reflection
- + Anti Moire effect

GOB is an improvement of traditional SMD technology, it is used for certain applications that require high-level protection of the LED front module. Used for broadcasting and virtual studios.

WATCH VIDEO



USA-BASED COMPANY

Panel ideal for indoor LED video walls. Stand out in all the events ahead of you.



TURN-KEY SOLUTIONS

LED video walls packages in stock, ready to ship immediately across the USA.



EASY INSTALLATION

Connect the power cable, your HDMI device to the video processor and the ethernet port.



TECHNICAL SUPPORT

We have online support with video tutorials, software, user guides, and specialized team.

TECHNICAL SPECIFICATIONS

| PIXEL PITCH | P2.5mm | |
|-------------------|---|--|
| LED ENCAPSULATION | King-Light SMD2020 | |
| PIXEL DENSITY | 200 x 200 | |
| SIZE | 500 x 500 x 82.5 mm / 19.7" x 19.7" x 3.25" | |
| CHIP | ICN1065 | |
| HIGH REFRESH RATE | 3840hz | |
| WEIGHT | 16 lb / pc - 7.5 kg | |
| RECEIVING CARD | NovaStar A8s-N | |









A8 NovaStar 3840 Hz

By NovaStar, single A8S-N supports resolutions up to 512×384@60Hz. Supporting various functions, can significantly improve the display effect and user experience.



POWER SUPPLY

Slim bar with noiseless technology.





19,7 inches (50 cm)

| MODULE 1 | MODULE 2 |
|----------|----------|
| MODULE 3 | MODULE 4 |

19,7 inches (50 cm)

FRONT + MODULE SIZE



9,8 in (25 cm)



3,25 in (8,25 cm)



9,8 in (25 cm) 1 in (2,5 cm)

| OPTICAL RATINGS | |
|-----------------------|-------------------------------|
| BRIGHTNESS | 800 NITS |
| PROTECTION RATE | IP45 |
| SCAN | 1/25s |
| FRAME FREQUENCY | 60 Hz |
| VIEW ANGLE | Horizontal 140°/Vertical 140° |
| OPTIMAL VIEW DISTANCE | 6 ft (1.8m) |
| BRIGHTNESS ADJUSTMENT | 0~100% 100 Levels |



MINIMUM VIEWING DISTANCE

WATCH VIDEO

OPTIMAL RANGE

Эft. 4 ft. 5 ft.

6 ft.

10 ft.

15 ft.

20 ft.

25 ft.

PIXEL PITCH (mm)

P1.53 P1.86 P1.99 P2.5

P2.97

P3.91


P4.81

P5











WALL MOUNTABLE

It is the most common support and above all the most stable considering the type of construction where it is mounted, since it is screwed through the holes included in our panels.

TRUSS SYSTEMS

Manufactured with heavy-duty aluminum material, ideal for overhead truss system, a ceiling grid, a crane, or other support structure from above.


GROUND SUPPORT

Bar and ladder truss that creates a stable system to support your screen in various configurations and offers flexibility in height as well as width.

| POWER SUPPLY | |
|------------------------|---|
| OPERATION POWER | 100~240V 50-60Hz |
| POWER CONSUMPTION | 200 W/pc |
| CONNECTIONS POWER/DATA | Power-PowerCon In/Out; Data EtherCon In/Out |



Easily removable magnetic module system to simplify assembly, repair or replacement of components. They can be removed with a special tool or manually.









LED NATION

- www.lednationusa.com
- info@lednationusa.com
- 1 (888) 590-1720
- STE 113 14501 NW 57th Ave, Opa-locka, FL 33054

OFFICIAL DEALER



